


MICRO SWITCH
 250V AC 6A RESISTIVE LOAD
 250V DC 0.5A RESISTIVE LOAD

COLOR : 10YR7.5/14
 DETECTION TORQUE : About 10.0N · cm
 REVOLUTION : 1RPM
 AMBIENT TEMPERATURE : -10 ~ +40°C

	POWER SUPPLY	APPLICATION TYPE DESIGNATION
	AC100V	PRL-5-WP
	AC200V	PRL-5-VP

*Please specify the cable gland type.

CABLE GLAND TYPE	Range of acceptable cable size
SXC-16B-1	φ 10 ~ φ 12
SXC-16B-2	φ 8 ~ φ 10



APPROVAL No.: T66814
 APPLICATION RANGE: d2G4
 EXPLOSION-PROTECTED CONSTRUCTION: D:d
 EXPLOSION CLASS: 2
 IGNITABILITY: G4

Q'ty:

図番 CHANGE NOTICE	承認 APPROVED	検図 CHECKED	製図 DRAWN ohno	名称 TITLE PRL-S7 PADDLE TYPE LEVEL SWITCH
	第三角法 THIRD ANGLE PROJECTION	尺度 SCALE 1:2	日付 DATE Mar, 2, 2016	図面番号 DRG. No. HR-91201
東和制電工業株式会社 TOWA SEIDEN INDUSTRIAL CO., LTD.				